

LED景观投光灯

LED Landscape Spot Light



WB3115R2*α-A3-X




WB3173R2*α-A3-X-06



WB3173R2*α-A3-X-09

Dimensions



产品简介Product Introduction

- 1.面盖:12# 压铸铝,表面喷涂处理
- 2.灯体:12#压铸铝, 表面喷涂处理
- 3.驱动:恒压输入
- 4.玻璃:高强度钢化玻璃, 抗冲击耐摩擦
- 5.配件:底座-铝/地插ABS

- 1.Front cover & Housing:12# Die-casting grey powder coated aluminum.T=60-80μm Adhesion of ISO class 1/ASTM class 4B high temperature painting
- 2.Driver:Constant current output,Constant current output
- 3.Glass:Step tempered glass
- 4.Base:aluminum
- Spike:ABS



Product specifications

Item No.	WB3115R2*α-A3-X/WB3115R3*α-A3-X	Item No.	WB3173R2*α-A3-X-06
LED source	CREE	LED source	CREE
Beam angle	10°/20°/30°/40°/60°	Beam angle	10°/24°/36°/60°
LED color	2200K/2700K/3000K/4000K/5000K/6000K	LED color	2200K/2700K/3000K/4000K/5000K/6000K
Power	3*2W	Power	6*2W
Input voltage	DC12V/DC24V H05RN-F-2*1.0mm² AC100~240V H05RN-F-3*0.75mm²	Input voltage	DC12V/DC24V H05RN-F-2*1.0mm² AC100~240V H05RN-F-3*0.75mm²
Operating temperature	-20℃~40℃	Operating temperature	-20℃~40℃
IK rate	08	IK rate	09
Luminance(lm)	Warm white=3811m/ Cool white=466lm	Luminance(lm)	Warm white=826lm/ Cool white=1100lm
Dimmable support	Triac/PWM/0-10V/DALI/DMX512	Dimmable support	Triac/PWM/0-10V/DALI/DMX512