

LED景观投光灯

LED Landscape Spot Light



WB3063R1*α-B4-M



WB3063R3*α-B4-M







WB3063R1*α-B4-B



WB3063R3*α-B4-B

Dimensions



产品简介Product Introduction

- 1.面盖:6063# 高散热航空铝,表面喷涂处理
- 2.灯体:6063#高散热航空铝, 表面喷涂处理
- 3.驱动:恒压输入
- 4.玻璃:高强度钢化玻璃, 抗冲击耐摩擦
- 5.配件:底座-铝/地插ABS



- 1.Front cover & Housing:12# Die-casting grey powder coated aluminum.T=60-80μm Adhesion of ISO class 1/ASTM class 4B high temperature painting
- 2.Driver:Constant current output,Constant current output
- 3.Glass:Step tempered glass
- 4.Base:aluminum
Spike:ABS

Product specifications

Item No.	WB3063R1*α-B4-B/WB3063R3*α-B4-B/WB3063R1*α-B4-M/WB3063R3*α-B4-M
LED source	CREE
Beam angle	25°/36°/60°
LED color	2700K/3000K/4000K/5000K/6000K
Power	1*6W
Input voltage	DC12V/DC24V H05RN-F-2*1.0mm ² AC100~240V H05RN-F-3*0.75mm ²
Operating temperature	-20℃~40℃
IK rate	03
Luminance(lm)	Warm white= m/ Cool white= lm
Dimmable support	Triac/PWM/0-10V/DALI/DMX512