

LED景观投光灯

LED Landscape Spot Light



WB3042R1*α-A3-M



WB3042R3*α-A3-M







WB3042R1*α-A3-B



WB3042R3*α-A3-B

Dimensions



产品简介Product Introduction

- 1.面盖: 6063# 高散热航空铝,表面喷涂处理
- 2.灯体: 6063#高散热航空铝, 表面喷涂处理
- 3.驱动: 恒压输入
- 4.玻璃: 高强度钢化玻璃, 抗冲击耐摩擦
- 5.配件: 底座-铝/地插ABS

- 1.Front cover & Housing:12# Die-casting grey powder coated aluminum.T=60-80μm Adhesion of ISO class 1/ASTM class 4B high temperature painting
- 2.Driver:Constant current output,Constant current output
- 3.Glass:Step tempered glass
- 4.Base:aluminum
- Spike:ABS



Product specifications	
Item No.	WB3042R1*α-A3-B/WB3042R3*α-A3-B/WB3042R1*α-A3-M/WB3042R3*α-A3-M
LED source	CREE
Beam angle	10°/20°/30°/40°/60°
LED color	2200K/2700K/3000K/4000K/5000K/6000K
Power	1*2W
Input voltage	DC12V/DC24V H05RN-F-2*1.0mm² AC100~240V H05RN-F-3*0.75mm²
Operating temperature	-20℃~40℃
IK rate	03
Luminance(lm)	Warm white=119m/ Cool white=140lm
Dimmable support	Triac/PWM/0-10V/DALI/DMX512